

C/C++ - File Edit Source Refactor Navigate Search Project Run Window Help 4:08 PM

VNA\_2\_205 - VNA\_/src/MODULES/M\_BCM2835\_SPI\_TFT/CBCM2835SPITFT.cpp - Eclipse

New Connection...

Quick Access

Console C/C++ Projects CBCM2835SPITFT. CBCM2835SPITFT. »4

```
953 cout << " Approximate read wait time "
954       << (ts_Read_End.tv_nsec - ts_Read_Start.tv_nsec)
955           / 1000 << " uS " << endl;
956
957
958 it << " Approximate write wait time "
959     << (ts_new.tv_nsec - ts_old.tv_nsec) / 1000 << " uS "
960     << endl;
961 it << " line " << __LINE__ << endl;
962 leep(100000); // 100 ms is observable flasing LED MOSI
963 it(1);
964 read and write counts shoul be same
965 (WriteCount != ReadCount) { //read and write counts shoul be same
966     cout << "read and write counts shoul be same" << endl;
967     cout << "WriteCount " << WriteCount << endl;
968     cout << "ReadCount " << ReadCount << endl;
969     exit(1);
970
971
972 > (! (SPI_CS_reg[0] & BCM2835_SPI0_CS_RXR)); // needs reading
973 < "BCM2835_SPI0_CS_RXR set " << __LINE__ << endl;
974 < " # of packets written " << WriteCount << endl;
```

Search

'ts\_loop\_Start' - 4 matches in 'CBCM2835SPITFT.cpp'

- VNA\_
  - src
    - MODULES
      - M\_BCM2835\_SPI\_TFT

Writable Smart Insert 965 : 81