

# BIRT API Change Control Document

<b>BIRT API Change Control Document .....</b>	<b>1</b>
<b>1. Introduction .....</b>	<b>1</b>
<b>2. Changed APIs:.....</b>	<b>1</b>
<b>3. Added APIs:.....</b>	<b>1</b>
<b>4. Removed APIs:.....</b>	<b>2</b>
<b>5. Miscellaneous Change Requests .....</b>	<b>3</b>

## 1. Introduction

Add new interface IReportEngine.getEmitterInfo(), which can be used to get information of the all the BIRT report emitter.

## 2. Changed APIs:

None

## 3. Added APIs:

### 3.1 Name : IReportEngine

Component name : org.eclipse.birt.report.engine

Package name : org.eclipse.birt.report.engine.api

Change Request:

#### 1. Add method:

`EmitterInfo[] getEmitterInfo ()`

Return information of all the BIRT report emitters, including:

- String format
- String id(emitter id)
- String pagination
- String mimeType
- String icon(the resource path of the emitter icon)
- String namespace(bundle id)

### 3.2 Name : EmitterInfo

Component name : org.eclipse.birt.report.engine

Package name : org.eclipse.birt.report.engine.api

**Change Request:**

1. Add method:

String getNamespace()

Return the namespace(bundle id) of the emitter bundle.

2. Add method:

String getIcon()

Return the icon path in the resource folder of the emitter bundle.

3. Add method:

String getFormat()

Return the output format of the emitter.

4. Add method:

String getId()

Return the emitter id of the emitter.

5. Add method:

String getMimeType()

Return the mime-type of the emitter.

6. Add method:

String getPagination()

Return the pagination of the emitter bundle.

7. Add method:

String getEmitter()

Return the emitter.

**Proposed Solution:**

According resolving **bug 159074**.

BIRT contributor can contribute their own report emitter followed the emitter extension. In order to display there own emitter icon contributed, add a new API named IReportEngine.getEmitterInfo() to get the necessary information of the emitter.

## 4. Removed APIs:

None

## **5. Miscellaneous Change Requests**

None.